

Ends of diagonals shall be cut to fit

t = chord wall thickness

3%" set screw -

at 90° intervals

Drill and tap wall

for 3/8" allen set screw

### CHORD SELECTION Sian Area Chord Size (X times Y) NOM DIA Wall $(f+)^2$ 50 or less .218′′ .203 150+ to 200 .216′′

Plate MIN

coatina)

x/2" slot for allen hollow

set screw with dog

point (corrosion

 $\frac{1}{2}$ " DIA steel bolt,  $\frac{1}{2}$ " long, with

washer and

nut for

ground.

resisting metal or

1. Vertical and horizontal clearance requirements shall be as

No post splices permitted in lower third of height, nor closer than  $3^{\prime}$ - $0^{\prime\prime}$  to bottom chord. No chord shop splices

permitted in first two-thirds of the span. Only one splice

permitted in post. For post or chord shop splice details, see Standard Plan "Sign Bridge".

All bolt holes shall be drilled, and the diameter shall be

 $V_{16}$ " larger than the nominal bolt diameter except as noted.

NOTES

POST SELECTION					
otal Sign Area*	Post Size				
Σ(X times Y)	OD	Wall			
(ft) <sup>2</sup>					
50 or less	16′′	.500′′			
50+ to 100	16′′	.500′′			
100+ to 150	18′′	.438′′			
150+ to 200	18′′	.500′′			
200+ to 250	20′′	.500′′			
250+ to 300	24′′	.375′′			
300+ to 350	24''	.438′′			
350+ to 400	24''	.500′′			

\*Sum of sign areas for doublecantilever

MATERIAL SPECIFICATIONS				
PIPE (Chords, Diagonals, Struts and Posts)	ASTM A 36 or ASTM A 53 Grade B, Type E or S, or A 500 Grade B			
PLATES & SHAPES	ASTM A 36			
BOLTS, NUTS, AND WASHERS	STD. SPEC. 9-06.5(3)			
PIPE, PLATE & SHAPE GALVANIZING	AASHTO M 111			
FASTENER GALVANIZING	AASHTO M 232			



## **SIGN STRUCTURES STANDARD PLAN G-3**

**CANTILEVER** 

SHEET 1 OF 1 SHEET


APPROVED FOR PUBLICATION








neatly against chords.



### END VIEW

All diagonals and struts shall be  $1\frac{1}{4}$ " pipe (0.140" wall)




CHORD TO POST CONNECTION

# snug fit FINIAL DETAIL Hand hole frame Round and smooth

Hemispherical Post Finial,  $\frac{1}{8}$  MIN thickness. Install after galvanizing.


Removable raintight hand hole cover with gasket. Fasten with two stainless steel (ASTM F-593) screws



HANDHOLE DETAIL


NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE THE ORIGINAL, SIGNED BY THE ENGINEER AND APPROVED FOR PUBLICATION, IS KEPT ON FILE
AT THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION. A COPY MAY BE OBTAINED

UPON REQUEST.			
03/2002	ADDED MATERIAL SPECIFICATIONS CORRECTED WELD SYMBOL	MAS	(
DATE	REVISION	BY	



at span end only

Bottom of lighting bracket -



Nipple, capped

L = 21' - 0'' MAX

ELEVATION

on side away from - approaching traffic

Hand hole on side away

from main roadway

elevation

Bottom of

base plate

POST BASE DETAIL